

## PRODUCT

### Ultra Premium Paint/Primer In One Interior Flat Finish

## DESCRIPTION

A premium interior 100% acrylic paint that is designed to meet the highest expectations of the most demanding consumer. This low odor, Low VOC, environmentally friendly product is Asthma and Allergy certified, Greenwise Gold certified, Master Painter Institute certified and approved for use by the US government.

## COLORS

|               |        |              |       |
|---------------|--------|--------------|-------|
| White         | EZF-1  | Pastel Base  | EZF-P |
| Off White     | EZF-8  | Tint Base    | EZF-T |
| Antique White | EZF-12 | Deep Base    | EZF-D |
| Black         | EZF-49 | Neutral Base | EZF-N |

## SURFACE PREP

See "Surface Prep" section for recommendations.

## APPLICATION

Do not apply over a surface that has not been thoroughly prepared. Stir thoroughly before and during use. Intermix all containers for color uniformity. Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator. Do not over spread. For best performance; apply two coats on new surfaces after priming.

## RECOMMENDED USES

Previously painted or properly prepared and primed interior surfaces. This product is Master Painter Institute certified and is approved for use by the United States Government.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spray application. Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant. Coverage of 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

|                          |                   |
|--------------------------|-------------------|
| Resin Type               | Acrylic           |
| Dry Time at 60°          | 0-5               |
| Weight per gallon        | 11.7 lbs/gal ± .2 |
| Percent solids by weight | 60.6 % ± 2%       |
| Percent solids by volume | 43.4 % ± 2%       |
| Viscosity Range          | 95-105 KU         |
| VOC                      | Less than 5 g/L   |
| MPI Certification        | 53                |

Revised: 05/2023

General Paint Manufacturing  
201 Jandus Road • Cary, Illinois 60013  
Phone: (800) 323-7545  
www.truevaluepaint.com

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.