

## PRODUCT

### Interior Ceiling Paint

## DESCRIPTION

A water based acrylic ceiling paint with a 15 year warranty when applied according to all label directions on a properly prepared surface.

## COLORS

CBW Bright White

## SURFACE PREP

Remove loose paint, wash off dirt and grease with proper cleaning solution. Scuff sand and dull glossy surfaces. Patch cracks and holes and spot primer. For heavily stained areas primer with a stain blocking primer (SRL-1).

## APPLICATION

Do not apply over a surface that has not been thoroughly prepared. Stir thoroughly before and during use. Intermix all containers for color uniformity. Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator. Do not over spread. For best performance; apply two coats on new surfaces after priming.

## RECOMMENDED USES

Previously painted or properly prepared and primed interior ceilings. Hides Minor imperfections.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spray application. Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant. Coverage up to 400 sq.ft. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic
Dry Time at 60°	1-3
Weight per gallon	11.3 lbs/gal
Percent solids by weight	48.0 ± .2
Percent solids by volume	28.5% ± 2% 28.5% ± 2%
Viscosity Range	95-100 KU
VOC	Less than 5 g/L
PVC	72.5%

Revised: 05/2023

General Paint Manufacturing  
201 Jandus Road • Cary, Illinois 60013  
Phone: (800) 323-7545  
www.truevaluepaint.com

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.