

PRODUCT

Ultra Premium Paint/Primer In One Interior Satin Finish

DESCRIPTION

A premium interior 100% acrylic paint that is designed to meet the highest expectations of the most demanding consumer. This low odor, Low VOC, environmentally friendly product is Asthma and Allergy certified, Greenwise Gold certified, Master Painter Institute certified and approved for use by the US government.

COLORS

White	EZSE-1	Pastel Base	EZSE-P
Off White	EZSE-8	Tint Base	EZSE-T
Antique White	EZSE-12	Deep Base	EZSE-D
		Neutral Base	EZSE-N

SURFACE PREP

See "Surface Prep" section for recommendations.

APPLICATION

Do not apply over a surface that has not been thoroughly prepared. Stir thoroughly before and during use. Intermix all containers for color uniformity. Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator. Do not over spread. For best performance; apply two coats on new surfaces after priming.

RECOMMENDED USES

Previously painted or properly prepared and primed interior surfaces. This product is Master Painter Institute certified and is approved for use by the United States Government.

ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spray application. Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant. Coverage of 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic
Dry Time at 60°	25-35
Weight per gallon	10.5 lbs/gal ± .2
Percent solids by weight	50.7% ± 2%
Percent solids by volume	35.9 % ± 2%
Viscosity Range	95-105 KU
VOC	Less than 5 g/L
MPI Certification	43

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.