

## PRODUCT

### Interior/Exterior Gloss Porch & Floor Coating

## DESCRIPTION

A low VOC, urethane fortified, ultra durable porch and floor coating with exceptional durability and a mildew resistant finish.

## COLORS

White	UGF-1	Tint Base	UGF-T
Light Gray	UGF-3	Deep Base	UGF-D
Tile Red	UGF-4	Neutral Base	UGF-N
Medium Gray	UGF-5		
Dark Gray	UGF-10		

## SURFACE PREP

Remove dirt, dust, grease and oil residue, loose and peeling paint or rust. Glossy areas must be dulled by sanding. Spot coat worn or bare areas. Allow new concrete to age 90 days before painting. Acid etch all bare concrete to the roughness of 100 grit sandpaper (this may require several etchings) before painting.

## APPLICATION

Stir or mix paint before using and intermix all containers for color uniformity. The dried film will become slippery when wet. The addition of a non-slip agent such as silica sand is recommended prior to application. Apply as-is with brush, roller or pad painter. For spraying information contact your paint specialist. Do not overspread. Surface temperature must be above 40°F (5°C).

## RECOMMENDED USES

Covered exterior wood, interior wood, and interior concrete. Use on porches, basement floors, utility rooms and other surfaces on which a wear-resistant coating is needed.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries to the touch in 2-8 hours. Recoat if necessary after 24 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant. Coverage of 250-450 sq. ft. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying. Properly Dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic/Polyurethane
Dry Time at 60°	60 +
Weight per gallon	10.30 lbs./gal
Percent solids by weight	44.0 %
Percent solids by volume	30.0 %
Viscosity Range	80-85 KU
VOC	Less than 100 g/L

Revised: 04/2023

General Paint Manufacturing  
201 Jandus Road • Cary, Illinois 60013  
Phone: (800) 323-7545  
www.truevaluepaint.com

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.