

PRODUCT

Interior Water-Based PVA Drywall Primer

DESCRIPTION

PVA Latex Primer is an excellent choice for priming new or unsealed drywall, ceilings, non-staining wood, plaster, stone, brick and concrete

COLORS

White PVA-1

SURFACE PREP

Remove loose paint, wash off dirt and grease with detergent. Allow to thoroughly dry. Scuff-sand and dull glossy surfaces. For best results on heavily stained areas, use a coat of Stain Blocking Primer (SRL-1). Do not use under semi-gloss or gloss paint.

APPLICATION

Stir thoroughly before and during use. Do not apply over a surface that has not been properly prepared. Use product when surface and air temperature are between 50°F – 90°F. Do not over spread. Use a high quality 3/8 inch nap roller cover or nylon/polyester brush. If applying by roller, roll from dry area into the wet using firm crisscrossing strokes. Finish with long ceiling to floor strokes in one direction. Paint the ceiling first, then the walls. Allow new masonry to cure at least 30 days before coating.

RECOMMENDED USES

New or unsealed interior drywall, non-staining wood, plaster, brick, stone and concrete surfaces.

ENVIRONMENTAL VARIABLES

Use as is. Dries in 1/2 hour. Topcoat after 2 hours. Allow 24 hours before sanding. Low temperature or high humidity may increase dry time. Coverage averages 350 sq. ft. per gallon.

CLEAN-UP

Use warm water and soap.

CAUTIONS

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Dry Time at 60°	2-4
Weight per gallon	11.0 lbs. ± .2
Percent solids by weight	44.9% ± 2 %
Percent solids by volume	26.9 % ± 2 %
Viscosity Range	95-105 KU
VOC	Less than 100 g/L

Revised: 04/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.