

PRODUCT

Interior/Exterior Water-Based Stain Blocking Primer

DESCRIPTION

Interior/Exterior Water-Based Stain Blocking Primer/Sealer great for blocking stains on drywall, paneling, wood, masonry and stucco.

COLORS

White SRL-1

SURFACE PREP

Remove dirt, grease ,wax and soap residue. Dull glossy areas with sandpaper. Patch cracks and holes then sand smooth when dry, then prime. New plaster must be properly cured before priming. New wood with tannic acid bleed may require Oil Base Primer/Sealer (SRO-1).

APPLICATION

Stir thoroughly before and during use. Do not apply over a surface that has not been properly prepared. Use product when surface and air temperature are between 50°F – 90°F. Do not over spread. Use a high quality 3/8 inch nap roller cover or nylon/polyester brush. If applying by roller, roll from dry area into the wet using firm crisscrossing strokes. Finish with long ceiling to floor strokes in one direction. Paint the ceiling first, then the walls. Allow new masonry to cure at least 30 days before coating.

RECOMMENDED USES

New or unsealed interior drywall, non-staining wood, plaster, brick, stone and concrete surfaces.

ENVIRONMENTAL VARIABLES

Use as is. Dries to the touch in 1-2 hours. Topcoat after two hours. Allow 24 hours before sanding. Low temperature or high humidity may increase dry time. Coverage averages 300-400 sq. ft. per gallon.

CLEAN-UP

Use warm water and soap.

CAUTIONS

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic Polymer
Dry Time at 60°	3-5
Weight per gallon	10.8 lbs. \pm .2 %
Percent solids by weight	50.5% \pm 2 %
Percent solids by volume	36.4 % \pm 2 %
Viscosity Range	95-105 KU
VOC	Less than 100 g/L
MPI	137

Revised: 04/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.