

PRODUCT

Floor Stripper

DESCRIPTION

- Dissolves old film to remove old waxes, finishes and sealers
- Ammonia free for more pleasant use
- Fast, effective formula resists creeping for easier use

RECOMMENDED USES

Maintenance One Floor Stripper features a heavy-duty formula. Add up to 16 ounces of stripper to a gallon of hot water for medium build up. Uniformly and liberally apply stripping solution to floor, but do not flood. Let stripper soak for 15 minutes, then scrub thoroughly with cold water. Not for use on glass, wood, aluminum or marble.

BENEFITS

Removes all acrylic and wax-based floor finishes along with soil, grease and grime. Completely rinseable with tap water. Also works as an excellent degreaser.

PACKAGING/SIZES

CONTAINER	MFG. NO.	STOCK NO.
1 qt	TV34	512886
1 gal	M34	512845
5 gal	M34	512795
55 gal	M34	512833

TECHNICAL SPECIFICATIONS

General appearance	Clear, light green
Fragrance	Mild lemon
Viscosity	Water thin
pH (as is)	Caustic
Storage stability	Over one year
Freeze/Thaw Stability	Passes three cycles

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.