

PRODUCT

Heavy Duty Cleaner/Degreaser

DESCRIPTION

- Powerful, concentrated grease-cutting formula
- Penetrates & lifts soils from the surface

RECOMMENDED USES

Maintenance One Heavy Duty Cleaner/Degreaser should be diluted 2 to 4 ounces per gallon of water. For light cleaning, apply with sprayer, mop, brush or sponge. For heavy build-up, allow to soak for several minutes and scrub where necessary. Wipe with a clean cloth, then rinse off with water. For medium cleaning, dilute 8 ounces per gallon of water. For heavy duty cleaning, dilute 24 ounces per gallon of water.

BENEFITS

Designed to clean and remove oil, grease, black heel marks, ink, tire marks from tile, wood and concrete.

PACKAGING/SIZES

CONTAINER	MFG. NO.	STOCK NO.
1 gal	M15	513546
5 gal	M15	513443

TECHNICAL SPECIFICATIONS

General appearance	Yellowish Orange
Fragrance	Orange
Viscosity	Thin
pH (as is)	Caustic
Storage stability	Over one year

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.