

PRODUCT

High Solids Floor Finish

DESCRIPTION

- Recommended for high speed, dry buff or spray buff maintenance methods
- Slip resistance for use on resilient and non-resilient floors
- Fast Drying, durable finish, resistant to detergent and scratching

RECOMMENDED USES

Maintenance One High Solids Floor Finish covers about 2,000 square feet per gallon. Prior to using, strip off all old wax and finish with a thorough rinse. Apply finish with mop, sponge or lamb's wool pad. Prior to recoat, let finish dry until completely tack free (20 to 40 minutes).

BENEFITS

For all types of resilient flooring including vinyl, vinyl composite, linoleum, asphalt or rubber tile, as well as sealed surfaces like terrazzo, concrete, wood and cork.

PACKAGING/SIZES

CONTAINER	MFG. NO.	STOCK NO.
1 gal	M33	512783
5 gal	M33	512795
55 gal	M33	512746

TECHNICAL SPECIFICATIONS

General appearance	Opaque emulsion
Fragrance	Mild
Viscosity	Water thin
pH (as is)	Caustic
Percent of solids	25.0 +- 0.5
Storage stability	Over one year
Freeze/Thaw Stability	Passes three cycles
Slip resistance	Over 0.7 (James Machine)

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.