

PRODUCT

Non-Buff Floor Finish

DESCRIPTION

- High gloss, self sealing finish without buffing or burnishing
- Ultra durable, scrubbable finish, resistant to scuffing and black heel marks
- Slip resistance for use on resilient and non-resilient floors
- U.L. Listed for slip resistance

RECOMMENDED USES

Maintenance One Non-Buff Floor Finish covers about 2,000 square feet per gallon. Prior to using, strip off all old wax and finish with a thorough rinse. Apply finish with mop, sponge or lamb's wool pad. Prior to recoat, let finish dry until completely tack free (20 to 40 minutes).

BENEFITS

Interlocked acrylic polymer for use on all types of resilient flooring including vinyl, vinyl composite, linoleum, asphalt or rubber tile, as well as sealed surfaces like terrazzo, concrete, wood and cork. Durable, scrubbable, non yellowing to keep its shine longer. Self-sealing and self-polishing.

PACKAGING/SIZES

CONTAINER	MFG. NO.	STOCK NO.
1 qt	TV32	512696
1 gal	M32	512684
5 gal	M32	512605
55 gal	M32	512643

TECHNICAL SPECIFICATIONS

General appearance	Opaque emulsion
Fragrance	Mild
Viscosity	Water thin
pH (as is)	Caustic
Percent of solids	20.0 +- 0.5
Storage stability	Over one year
Freeze/Thaw Stability	Passes three cycles
Slip resistance	Over 0.6 (James Machine)

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.