

## PRODUCT

### Painter's Select Interior/Exterior Semi-Gloss Finish

## DESCRIPTION

A quality interior/exterior acrylic paint.

## COLORS

White	CPSG-1
Pastel Base	CPSG-P
Tint Base	CPSG-T
Deep Base	CPSG-D
Neutral Base	CPSG-N

## SIZES

Quart, Gallon, 5 Gallon

## SURFACE PREP

Remove loose paint, wash off dirt and grease with detergent. Remove wallpaper. Scuff sand and dull glossy surfaces. Patch cracks and holes and spot prime. For heavily stain areas prime with Stain Blocking Primer (SRL-1).

## APPLICATION

Do not apply over a surface that has not been thoroughly prepared. Stir thoroughly before and during use. Intermit for color uniformity. Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator. Do not over spread. For best performance; apply two coats on new surfaces after priming.

## RECOMMENDED USES

Previously painted or properly prepared and primed interior & exterior surfaces. Perfect for kitchens, bathrooms, and areas that need constant washings.

## ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries to the touch in 1-2 hours. Recoat if necessary, after 4 hours. High humidity or low temperature may increase dry time. A After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant. Coverage of 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

## CLEAN-UP

Wash tools with warm water and soap immediately after applying.

## CAUTIONS

Properly dispose of all soiled rags. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

Resin Type	Acrylic
Dry Time at 60°	35-45
Weight per gallon	9.7 ± .2 lbs/gal
Percent solids by weight	40.1 ± 2 %
Percent solids by volume	31.9 ± 2 %
Viscosity Range	95-105 KU
VOC	Less than 50 g/L

Revised: 04/2023

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.