

PRODUCT

**Painter's Select Pro Best
Interior Semi-Gloss Finish**

DESCRIPTION

Our best quality latex Semi-Gloss contractor grade finish.

COLORS

Pastel Base 200S

SURFACE PREP

Inadequate surface prep accounts for about 90% of all paint failures. The surface must be free of dust, dirt, chalk and grime. Damaged wood must be repaired or replaced. Cracks, gaps and holes can be filled with spackle or drywall compound. Glossy surfaces need to be sanded and wiped.

APPLICATION

Do not apply over a surface that has not been thoroughly prepared. Mix thoroughly before using and stir occasionally during application. Intermit all containers for color uniformity. Use a premium brush, roller or pad applicator. May be spray applied. Do not over spread. For best performance; apply two coats on new surfaces after priming.

RECOMMENDED USES

Previously painted or properly prepared and primed interior surfaces.

ENVIRONMENTAL VARIABLES

Thin sparingly with water if necessary for spraying. Dries in 30 minutes. Recoat if necessary after two hours. High humidity or low temperature may increase dry time. Coverage of 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN-UP

Wash tools with warm water and soap immediately after applying.

CAUTIONS

Do not expose this product to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

| | |
|--------------------------|-----------------|
| Resin Type | Vinyl Acrylic |
| Dry Time at 60° | 23-33 |
| Weight per gallon | 9.8 lbs. |
| Percent solids by weight | 36.0 % |
| Percent solids by volume | 25.5 % |
| Viscosity Range | 95-105 KU |
| VOC | Less than 5 g/L |
| MPI | 43 |

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.