

PRODUCT

**Oil Based Interior Poly + Stain
 Varnishes**

RECOMMENDED USES

New or previously stained or varnished wood such as, furniture, trim, paneling, doors, cabinets and woodwork.

COLORS & FINISHES

Colors: Espresso, Pecan, Bombay Mahogany, GPS – Gloss
 Classic Oak, Mission Oak, Antique Walnut, SPS – Satin
 American chestnut, Honey, Classic Black

APPLICATION

Do not apply over a surface that has not been thoroughly and properly prepared. Stir thoroughly before use, **DO NOT SHAKE**. Use quality natural brush or pad applicator. When applying over unvarnished stained or unfinished wood; rub with 0000 steel wool or 120 grit sandpaper then wipe clean with a tack cloth. Apply one or more coats to achieve the desired appearance. For application over previously varnished surfaces that have been properly prepared apply one or two coats. **DO NOT** apply over lacquer or shellac. Always maintain a wet edge to avoid lap marks. Be sure to allow adequate dry time between coats.

LIMITATIONS

Not intended for exterior use. Do not expose this product to excessive heat. Do not use over non-wood surfaces. Close container after each use. Not for use on floors. Do not thin.

ENVIRONMENTAL VARIABLES

Dry times at 70-80F and 50% humidity are set to touch in 30-45 minutes and tack free in 2 hours. Recoat after 2 hours. Dries overnight under normal conditions. High humidity or low temperature may increase dry time. Coverage of 600-700 Sq. FT / Gallon

SIZES

One Quart, Half Pint

CLEAN-UP

Wash tools with mineral spirits or paint thinner immediately after applying.

CAUTIONS

DO NOT apply over lacquer or shellac. Always maintain a wet edge to avoid lap marks. Be sure to allow adequate dry time between coats.

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Flashpoint	Greater than 104°F (40°C)
Dry Time at 60°	80-100
Dry Film Thickness	1-2 mil
Wet Film Thickness	2.5 to 5 mil
Viscosity Range	50 – 70 KU
VOC	450 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.