

## PRODUCT

### Premium Décor Decorative Finish Gloss Enamel

## DESCRIPTION

Superior interior/ exterior decorative enamel spray at any angle, comfort spray tip.

## COLORS

Gloss White	PDS-1	Daffodil	PDS-41
Gloss Black	PDS-2	Emperial	PDS-45
Clear Acrylic Gloss	PDS-7	Majestic Oak	PDS-46
Navajo White	PDS-11	Windowept	PDS-47
Ivory	PDS-12	Paisley Blue	PDS-48
Heirloom White	PDS-15	Calypso	PDS-49
Almond	PDS-16	Hunter Green	PDS-50
Coastal Calm	PDS-19	Dragonfly	PDS-51
Awareness Pink	PDS-20	Meadow Green	PDS-52
Banner Orange	PDS-24	Leather Brown	PDS-60
Americana	PDS- 29	Slate Gray	PDS-70
Royal Blue	PDS-30	Pewter Gray	PDS-71
Harbor Blue	PDS-31	Shutter Red	PDS-95
Granite	PDS-32	Fiesta Red	PDS-96
Safari	PDS-36	Hot Red	PDS-97
Autumn Fern	PDS-37	Caribbean Water	PDS-100
Pink Punch	PDS-38	Pumpkin Orange	PDS-101
Wild Lilac	PDS-39	Apple Green	PDS-102
Sunflower Yellow	PDS-40	Plum Purple	PDS-103

## SURFACE PREP

Remove all grease, oil, dirt, wax and rust scale from surface. On new clean surface no primer is necessary. For rusty metal surfaces prime with X-O Rust Primer. New galvanized surfaces must weather 6 months before priming. Use with adequate ventilation.

## APPLICATION

Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use. Hold can 10" to 18" (25 to 45 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke. Keep can in motion while spraying. Recoat within one hour.

## RECOMMENDED USES

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

## ENVIRONMENTAL VARIABLES

Set to touch in 0-10 minutes. Tack free 20-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time. Contains no CFC's which deplete the ozone layer

## CLEAN-UP

Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

## CAUTIONS

Contains propane, acetone and aromatic solvents. Extremely flammable. Storage and handling: Level-3 Aerosols. Do not use on Styrofoam, ceramic tiles or marble. Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

VOC - Gloss	Max 65% VOC & 0.95 pw MIR
VOC - Clear	Max 67% VOC & 0.85 pw MIR
Flashpoint	< 20° F
Percent solids by weight	PDS-1 19.65% + - 2
Dry Time at 60°	80 Minutes

Revised: 04/2023

General Paint Manufacturing  
201 Jandus Road • Cary, Illinois 60013  
Phone: (800) 323-7545  
www.truevaluepaint.com

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.