

PRODUCT

Rental One High Traffic Pre-Treat

DESCRIPTION

Rental High Traffic Pre-Treatment penetrates and lifts seated soil. Helps raise trampled carpet. Great for hallways and entranceways and any high traffic zone.

RECOMMENDED USES

Use on hallways, stairs, entranceways and other heavily soiled areas.

APPLICATION

A pre-conditioner that loosens soil and dirt in traffic lanes such as hallways, stairs, entranceways and other heavily soiled areas. Pre-spray in conjunction with carpet extraction or use as a spot remove for beverage, food, grease, ink and paint stains. Meets or exceeds carpet manufacturer's specification for cleaning stain-resistant carpets. Not recommended for use on upholstery. Designed for use with all carpet extraction machines.

DIRECTIONS

PRE-SPRAY TRAFFIC LANES:

- Spray on any heavily soiled area – avoid over wetting carpet
- Allow to work on an area for 2 to 5 minutes
- Allow carpet to dry. Drying time can be reduced by using a blower or several fans

SPOT REMOVAL:

- Act as quickly as possible. The longer a spill is neglected the more difficult the removal process
- Spray directly on area as soon as stain is detected
- Allow to work for 1 - 3 minutes
- Blot area with a clean white towel, always working from the edge of the spill to the center
- DO NOT SCRUB THE AREA!
- Allow area to dry. To speed drying, apply a ½ inch layer of white paper towels to area and weigh down with a flat, heavy object
- If stain is not completely removed, repeat procedure

TIPS

Vacuum carpet thoroughly. Before cleaning carpet, test product in a small hidden place for colorfastness or shrinkage. When using any product on stain-resistant carpeting, check manufacturer's recommendations for use. Do not mix with bleach or any other household chemicals.

DISPOSAL

Use up or give away excess product. Contains surfactants. Do not reuse container. Empty container may be recycled or placed in trash.

STORAGE

Avoid extreme temperatures. Store in a cool, dry area. Close container after each use. If frozen, thaw and mix before use.

TECHNICAL SPECIFICATIONS

Percent solids by weight	4 to 5.5 %
Weight per Gallon	8.4 +/- 0.1lb
Viscosity	Water thin

SIZE

32 OZ.

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.