

PRODUCT

TruStripe Fast Dry Exterior Latex Zone Marking Paint

DESCRIPTION

Exterior Latex Fast Dry Zone Marking paint ideal for marking curbs, parking lots, factory floors and warehouses. For best results apply with automatic marking equipment.

COLORS

White	1033
Yellow	1034
Black	1035
Red	1036
Blue	1037
Green	1038

SURFACE PREP

Clean surface to remove dirt, grease, oil and loose and peeling paint. When applied over emulsified coal tar compounds and sealers the surface must first age 7 days.

APPLICATION

Stir paint before and during use. Apply with brush, marking roller or line striping equipment. No thinning is necessary (see paint specialist for details). Avoid marking if surface temperature is below 50°F (5°C) or rain is expected.

RECOMMENDED USES

For marking curbs and safety zones on streets and parking lots. May also be used for marking playgrounds, tennis courts, safety and storage areas in factories and warehouses.

COVERAGE

<u>Width of line</u>	<u>Linear feet per gallon</u>
3" (76.2mm)	600 feet (187 meters)
4" (101.6 mm)	450 feet (137 meters)
5" (127 mm)	350 feet (110 meters)
6" (152.4 mm)	300 feet (91 meters)

Coverage is based on applying the average wet film at 13 mils 125 sq. ft. per gallon.

ENVIRONMENTAL VARIABLES

Thin only if necessary; using water and not exceeding 1 pint per gallon. Dries to the touch in 14 minutes. Sets up in 10 to 20 minutes. High humidity or low temperature may increase dry time.

CLEAN-UP

Wash tools with warm water and soap immediately after applying followed by mineral spirits if using striping equipment.

CAUTIONS

Protect unused product from freezing. Properly dispose of all soiled rags.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Dry Time at 60°	0-9
Weight per gallon	14.7 ± 0.5 lbs
Percent solids by weight	73.1% ± 2%
Percent solids by volume	59.2% ± 2%
Viscosity Range	80-90 KU
VOC	Less than 50 g/L

Revised: 04/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.