

PRODUCT

TruStripe Exterior Latex Field Marking Paint

DESCRIPTION

Exterior Latex Field Marking Paint in a variety of colors. For natural and artificial turf. Can also be tinted for special team colors.

COLORS

White	TS-ALL 2
Red	TS-ALL 3
Blue	TS-ALL 4
Yellow	TS-ALL 5
Black	TS-ALL 6
Green	TS-ALL 11
Neutral Base	TS-N

APPLICATION

One gallon will cover grass at a rate of approximately 1200 feet with a 4 inch stripe, 1500 feet with a 4 inch stripe on smooth surfaces. Avoid applying if rain or dew is expected or if the temperature is below 50° F. Stir and mix before and during use.

RECOMMENDED USES

Intended for use on athletic surfaces such as baseball diamonds, football, soccer fields, volleyball, badminton and tennis courts. Can be used on artificial surfaces.

ENVIRONMENTAL VARIABLES

Thin 4:1 paint to water when using a striping machine. Dries in approximately 1 hour. High humidity or low temp may increase dry time.

CLEAN-UP

Tools, drips and spills should be cleaned with soap and water immediately.

CAUTIONS

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Vinyl Acrylic
Dry Time at 60°	0-5
Weight per gallon	10.2 lbs/gal
Percent solids by weight	31.9 %
Percent solids by volume	16.1 %
Viscosity Range	90-100 KU
VOC	Less than 5 g/L

Revised: 04/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.