

PRODUCT

TruStripe Exterior Oil Base Zone Marking Paint

DESCRIPTION

Exterior Oil Base Zone Marking Paint is ideal for marking curbs, parking lots, factory floors and warehouses. For use with automatic marking equipment.

COLORS

White	1010
Yellow	1012

SURFACE PREP

Clean surface to remove dirt, grease, oil and loose and peeling paint. When applied over emulsified coal tar compounds and sealers the surface must first age 7 days.

APPLICATION

Stir paint before and during use. Apply with brush, marking roller or line striping equipment. No thinning is necessary (see paint specialist for details).

RECOMMENDED USES

For marking curbs and safety zones on streets and parking lots. May also be used for marking playgrounds, tennis courts, safety and storage areas in factories and warehouses.

COVERAGE

<u>Width of line</u>	<u>Linear feet per gallon</u>
3" (76.2mm)	600 feet (187 meters)
4" (101.6 mm)	450 feet (137 meters)
5" (127 mm)	350 feet (110 meters)
6" (152.4 mm)	300 feet (91 meters)

Coverage is based on applying the average wet film at 13 mils 125 sq. ft. per gallon.

ENVIRONMENTAL VARIABLES

Do NOT thin. Dries/sets to touch in 10-20 minutes. High humidity or low temperature may increase dry time.

CLEAN-UP

Wash tools with mineral spirits (paint thinner).

CAUTIONS

Do not expose this container to excessive heat. Close container after each use.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Alkyd
Dry Time at 60°	1-4
Weight per gallon	10.87 lbs
Percent solids by weight	66 %
Percent solids by volume	49 %
Viscosity Range	75-80 KU
VOC	Less than 450 g/L

Revised: 04/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.