

PRODUCT

Exterior 100% Acrylic Semi-Transparent Deck, Siding & Fence Stain - STL

DESCRIPTION

100% Acrylic Semi-Transparent Deck, Siding & Fence Stain for natural or pressure treated wood decks, siding & fences. Helps wood stand up to the harshest weather elements

RECOMMENDED USE

Exterior above ground natural & pressure-treated woods including cedar, redwood, fir and pine. Also provides excellent protection while maintaining natural appearance to siding, shakes, wood shingles, landscape timbers and decks. MPI approved.

APPLICATION METHOD

Apply only to bare wood surfaces that have been properly prepared and cleaned. **ONLY ONE COAT IS RECOMMENDED.** Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 50° F. Do not apply in hot sun. Stir thoroughly before and during use. Intermix all containers for uniform color. Use a premium brush or pad applicator. A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood. **DO NOT OVER APPLY.** Spread well, do not puddle or accumulate on wood surface. Moving left to right, apply to two or three boards at a time leaving a “wet edge” to prevent lapping. Saturate end grain.

ENVIRONMENTAL VARIABLES

DO NOT THIN. 77° F @50% humidity: Dry to the touch within 2 to 4 hours. Recoat within 24 hours. High humidity or low temperatures may increase dry time. Tinting capability in limited number of colors. Coverage of 150-250 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat, depending on the porosity of the wood.

CLEAN-UP

Wash tools with warm water and soap immediately after application.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

| | |
|--------------------------|-------------------|
| Resin Type | Acrylic Latex |
| Dry time @ 60° | 0-20 |
| Weight per gallon | 8.8 lbs. |
| Percent Solids by weight | 17.8 |
| Percent Solids by volume | 12.9 |
| Viscosity Range | 55-65 KU |
| VOC | Less than 100 g/L |

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.