

**PRODUCT**

**Exterior Semi-Transparent Oil Deck,  
 Siding & Fence Stain - STOV**

**DESCRIPTION**

Oil Base Semi-Transparent Deck, Siding & Fence Stain for natural or pressure treated wood decks, siding & fences.

**RECOMMENDED USE**

Exterior above ground natural & pressure-treated structures such as decks, shingles, shakes, clapboard, wood siding, rough sawn siding and plywood, wood railings and landscape timbers. Not recommended for trim. Two coats may result in a higher sheen. MPI approved.

**APPLICATION METHOD**

Apply only to bare wood surfaces that have been properly prepared and cleaned. **ONLY ONE COAT IS RECOMMENDED.** Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 50° F. Do not apply in hot sun. Stir thoroughly before and during use. Intermix all containers for uniform color. Use a premium brush or pad applicator. A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood. **DO NOT OVER APPLY.** Spread well, do not puddle or accumulate on wood surface. Moving left to right, apply to two or three boards at a time leaving a "wet edge" to prevent lapping. Saturate end grain.

**ENVIRONMENTAL VARIABLES**

Dries thoroughly usually within 24 hours. High humidity or low temperatures may increase dry time. (DO NOT THIN). Tinting capability in limited number of colors. Coverage of 100-400 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat depending on the porosity of the wood.

**CLEAN-UP**

Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags.

**CAUTIONS**

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**PHYSICAL PROPERTIES**

Resin Type	Soya Alkyd/Acrylic Latex
Dry time @ 60°	20-35
Weight per gallon	8.60 lbs.
Percent Solids by weight	27.0
Percent Solids by volume	24.3
Viscosity Range	25-35 sec.
VOC	Less than 250 g/L

Revised: 05/2023

General Paint Manufacturing  
 201 Jandus Road • Cary, Illinois 60013  
 Phone: (800) 323-7545  
 www.truevaluepaint.com

**Limited Warranty**

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.