

PRODUCT

Exterior Solid Color Siding & Fence Stain - WSOV

DESCRIPTION

Oil Base Solid Color Siding & Fence Stain for natural or pressure treated wood siding & fences.

RECOMMENDED USE

Exterior above ground natural & pressure-treated structures such as wood siding, fences, shingles, shakes, clapboard, rough sawn siding and plywood. Not recommended for decks.

APPLICATION METHOD

DO NOT APPLY TO DECKS. Apply only to properly prepared and cleaned wood surfaces. On non-porous surfaces apply only one coat, as two coats may result in a high sheen finish. On very porous or severely weathered wood two coats may necessary. Do not apply if rain or dew is expected within 48 hrs or if outside temperature could drop below 40° F. Do not apply in hot sun. Stir thoroughly before and during use. Intermix all containers for uniform color. Use a premium brush or pad applicator. A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood. DO NOT OVER APPLY. Spread well, do not puddle or accumulate on wood surface. Moving left to right, apply to two or three boards at a time leaving a “wet edge” to prevent lapping. Saturate end grain.

ENVIRONMENTAL VARIABLES

Allow 12-15 hours between coats. Dries thoroughly usually within 24 hours. High humidity or low temperatures may increase dry time. (DO NOT THIN). Fully tintable. Coverage of 150-350 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon depending on the porosity of the wood.

CLEAN-UP

Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic modified alkyd
Dry time @ 60°	0-15
Weight per gallon	9.20 lbs.
Percent Solids by weight	28.80
Percent Solids by volume	21.50
Viscosity Range	77-83 KU
VOC	Less than 250 g/L

Revised: 05/2023

General Paint Manufacturing
 201 Jandus Road • Cary, Illinois 60013
 Phone: (800) 323-7545
 www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.