

PRODUCT

Exterior Latex Redwood Stain –LRW-1

DESCRIPTION

Painter's Select Specialty Exterior Flat Latex Redwood Stain

RECOMMENDED USE

Exterior above ground natural wood such as fencing, siding, shakes & shingles. NOT TO BE USED ON DECKS, PATIOS AND ANY AREA WALKED ON.

APPLICATION METHOD

DO NOT APPLY TO DECKS. Apply only to properly prepared and cleaned wood surfaces. On redwood, cedar, rough fir or pine siding an exterior oil Based Primer must be applied to prevent bleeding into the topcoat. On non-porous surfaces apply only one coat, as two coats may result in a high sheen finish. On very porous or severely weathered wood two coats may necessary. Do not apply if rain or dew is expected within 48 hrs or if outside temperature could drop below 50° F. Do not apply in hot sun. Stir thoroughly before and during use. Intermit all containers for uniform color. Use a premium brush or pad applicator. A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood. DO NOT OVER APPLY. Spread well, do not puddle or accumulate on wood surface. Moving left to right, apply to two or three boards at a time leaving a "wet edge" to prevent lapping. Saturate end grain.

ENVIRONMENTAL VARIABLES

DO NOT THIN. Dries thoroughly within 4 hours. Allow 12-15 hours between coats. High humidity or low temperatures may increase dry time. Coverage of 250-400 sq. ft. (33 square meters) per gallon (3.78L) first coat depending on the porosity of the wood.

CLEAN-UP

Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Weight per gallon	8.60 lbs/gal
Percent Solids by weight	8.94%
Percent Solids by volume	7.17%
Viscosity Range	75-80 KU
VOC	Less than 50 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.