

PRODUCT

Woodsman Revive Deck Coating

DESCRIPTION

A water based Solid Color Deck, Wood and Concrete restoration coating for natural or pressure treated wood decks, patio blocks and concrete. Helps restore old wood and concrete.

RECOMMENDED USE

Exterior above ground natural or pressure-treated wood structures such as decks, steps, as well as concrete walkways, masonry and cement patios.

APPLICATION METHOD

Apply only to properly prepared and cleaned wood surfaces. Stain two boards at a time going across the entire length. Keep a wet edge. On very porous or severely weathered wood two coats may be necessary. Do not apply if rain or dew is expected within 48 hours or if outside temperature could drop below 50° F. Do not apply in hot sun. Stir thoroughly before and during use. Intermix all containers for uniform color. Use a premium brush or pad applicator. **DO NOT OVER APPLY.** Spread well, do not puddle or accumulate on wood surface.

ENVIRONMENTAL VARIABLES

DO NOT THIN. Dry to the touch within 24 hours. Recoat usually within 4-6 hours. High humidity or low temperatures may increase dry time. Wait 3-5 days before placing furniture or heavy objects on newly painted surface. Coverage of 50 sq. ft. per gallon first coat, 50 sq. ft. per gallon second coat, depending on the porosity of the wood.

CLEAN-UP

Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Alkyd, Elastomeric, Acrylic
Dry time @ 60°	3-8
Weight per gallon	11.25
Viscosity Range	N/A
VOC	Less than 100 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.