

## PRODUCT

### Tru-Seal Clear Multi-Surface Waterproofing Sealer – CS-1

## DESCRIPTION

Penetrates and protects wood, masonry and concrete

## RECOMMENDED USE

Protects wood, concrete, masonry, brick, composition surfaces, and other porous surfaces.

## SURFACE PREP

Surfaces must be clean, dry and porous. Surface is suitable for application if a small amount of water can be quickly absorbed.

## APPLICATION METHOD

Apply by brush, roller, dip or spray without thinning. A garden sprayer is suitable for spraying. Apply liberally in a uniform manner. If too much is applied, a non-drying residue will form. This may be removed by wiping with a rag. Test for compatibility prior to application. Average coverage is 100 to 200 sq. ft (9 to 19 square meters) per gallon (3.78L) depending on surface porosity. **DO NOT APPLY OVER PAINT, RECENTLY STAINED SURFACES, VARNISH, RUBBER, PLASTIC, ASPHALT OR SEALED SURFACES. DO NOT USE AS AN ADDITIVE. DO NOT BLEND OR MIX WITH OTHER TRU-SEAL WATER-PROOFING PRODUCTS.**

## ENVIRONMENTAL VARIABLES

Typically dries in 24-48 hours for a single coat. If a second coat is needed, allow 48 hours before application. Do not apply paint, stain or varnish over Tru-Seal, or use as an additive to any coating. Do not apply over rubber, plastic, asphalt, canvas or sealed surfaces.

## CLEAN-UP

Clean up tools, drips and spills immediately with mineral spirits (paint thinner). Properly Dispose of all soiled rags.

## CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

## PHYSICAL PROPERTIES

|                          |                   |
|--------------------------|-------------------|
| Weight per gallon        | 6.68 pounds       |
| Percent Solids by weight | 25.13%            |
| Percent Solids by volume | 21.83%            |
| Viscosity Range          | 6"-12" Ford Cup   |
| VOC                      | Less than 600 g/L |

Revised: 05/2023

### Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.