

PRODUCT

Tru-Seal Exterior Water Based Multi-Surface Waterproofing Sealer – TS-1

DESCRIPTION

Multi-Surface Waterproofing Sealer penetrates the surface and provides optimal protection against water damage while providing a mildew resistant film.

RECOMMENDED USE

Apply on new or weathered exterior wood, decks, fences, outdoor wood furniture and weathered masonry surfaces including brick & concrete. May also be applied on siding (solid wood and plywood, including T-1-11). For exterior use only.

APPLICATION METHOD

CAUTION: Surfaces are slippery when wet. Use caution when walking on wet surfaces during application. **DO NOT THIN.** Apply when air and surface temperature is between 50° F (10° C) – 80° F (27° C). Do not apply in hot sunlight or if cold, wet weather is expected within 48 hours. Apply with a synthetic brush, roller (synthetic woven 3/8"-3/4" nap depending on surface texture) or garden sprayer. Apply an even coat, avoiding heavy application. If ponding occurs, remove within 15 minutes of application by redistributing to dry areas or wiping off. **ONLY ONE LIGHT COAT IS NECESSARY IN MOST APPLICATIONS.** After product is completely dry do "splash test: to determine if second coat is needed. If an additional coat is required, it may be applied after four to six hours and before 24 hours have passed. Tackiness will result if over applied. This may also occur if air or surface temperature fall below 40° F within 48 hours after application.

ENVIRONMENTAL VARIABLES

At 77° F (25° C) and 50% RH, dries to light foot traffic in 24 to 48 hours depending on temperature and humidity. Low temperature, high humidity, thick films or poor ventilation will increase these times. Avoid heavy abrasions immediately following application. Coverage on rough surfaces, 75-125 sq. ft./gallon (1.8-3.0 m2/L); on smooth surfaces 125 – 250 sq. ft./gallon (3.0-6.0 m2/L). Coverage will vary depending on the type, age and texture of the substrate.

CLEAN-UP

Clean hands and tools immediately with warm soapy water. Clean spills right away with a damp cloth. Dried product can be removed with mineral spirits. Properly Dispose of all soiled rags.

CAUTIONS

Keep from freezing. Do not expose this container to excessive heat. Close container after each use.

Disposal - Full: Give remaining product to neighbors or community organization. **Partially full:** (If state or local regulations allow) Pour residue into absorbent material. **When dry,** dispose of in trash for pick up. **Empty:** This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Weight per gallon	6.68 pounds
Percent Solids by weight	25.13%
Percent Solids by volume	21.83%
Viscosity Range	6"-12" Ford Cup
VOC	Less than 80 g/L

Revised: 05/2023

General Paint Manufacturing
201 Jandus Road • Cary, Illinois 60013
Phone: (800) 323-7545
www.truevaluepaint.com

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.