

PRODUCT

Exterior 100% Acrylic Wood Toned UV Sealant & Protector - WTSP

DESCRIPTION

100% Acrylic Water Repellent for natural or pressure treated wood decks & siding.

RECOMMENDED USE

Exterior above ground natural & pressure-treated woods, including cedar, redwood, fir and pine. Ideal for wood siding, decks and all exterior wood surfaces.

APPLICATION METHOD

Stir and mix product before and during use. Intermix all containers to assure uniformity. Test for penetration. Apply as is with brush, roller, pad or spray. Back brush immediately if roller or spray applied. **DO NOT THIN.** Only one coat is recommended. Apply water repellent 2 or 3 boards at a time going across the entire length, keeping a wet edge. Avoid treating wood if temperature is below 50° F (10° C) or rain is expected within 24 hours. Do not apply over a surface that has not been thoroughly prepared. Do not apply indoors.

ENVIRONMENTAL VARIABLES

DO NOT THIN. Usually dries within 24 hours. High humidity or low temperatures may increase dry time. Coverage of 150-350 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat depending on the porosity of the wood.

CLEAN-UP

Wash tools with warm water & soap immediately after application. Properly dispose of all soiled rags.

CAUTIONS

Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Resin Type	Acrylic Latex
Weight per gallon	8.43 lbs/gal
Percent Solids by weight	8.19%
Percent Solids by volume	7.21%
Viscosity Range	65-70 KU
VOC	Less than 100 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.