

PRODUCT

**Oil Based Penetrating Interior
 Wood Stains**

RECOMMENDED USES

Interior wood surfaces such as furniture, trim, paneling, doors, cabinets, floors and woodwork.

FINISHES

Dark Walnut	IS-1	Cherry	IS-10
Golden Oak	IS-2	Classic Gray	IS-11
Early American	IS-3	Carbon Gray	IS-12
Red Mahogany	IS-4	Weathered Oak	IS-13
Walnut	IS-5	Red Chestnut	IS-14
Provincial	IS-6	Antique White	IS-15
Natural	IS-7	Blue Jeans	IS-16
Ebony	IS-8	Barn Red	IS-17
Jacobean	IS-9		

APPLICATION

Apply stain in the direction of wood grain with good quality natural brush or clean cloth. Allow stain to penetrate for 3-10 minutes to achieve desired color. Remove any stain which did not penetrate in the wood with clean cloth. Always wipe in the direction of grain blending dark and light areas for uniform color. Do not allow stain that has not penetrated to dry or puddle on the surface. To darken color, apply second or third coat if necessary. Do not sand between coats and follow application direction for each coat. Allow 1 hour between coats. Apply clear protective finish after 2 hours.

LIMITATIONS

Not intended for exterior use. Do not expose this product to excessive heat. Do not use over non-wood surfaces. Close container after each use. Not for use on floors. Do not thin.

ENVIRONMENTAL VARIABLES

Dry times at 70-80F and 50% humidity are set to touch in 10-15 minutes and tack free in 1 hour. Recoat after 1.5 - 2 hours. High humidity or low temperature may increase dry time. Coverage of 500-600 Sq. FT / Gallon

SIZES

One Quart, Half Pint

CLEAN-UP

Wash tools with mineral spirits or paint thinner immediately after applying.

CAUTIONS

DO NOT apply over polyurethane finishes. Always maintain a wet edge to avoid lap marks. Be sure to allow adequate dry time between coats.

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Flashpoint	Greater than 100°F (38°C)
Viscosity Range	10 – 20 Seconds #4 Ford
VOC	250 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.