

PRODUCT

Oil Based Pre-stain Wood Conditioner

RECOMMENDED USES

Prepares bare wood for staining. New interior wood surfaces such as, furniture, trim, paneling, doors, cabinets and woodwork.

APPLICATION

Do not apply over a surface that has not been thoroughly and properly prepared. Stir thoroughly before use, **DO NOT SHAKE**. Use quality natural brush or pad applicator. When applying over unvarnished or unfinished wood; rub with 0000 steel wool or 120 grit sandpaper then wipe clean with a tack cloth. Apply one coat liberally. Allow to penetrate for 5 – 15 minutes, then remove excess with a clean cloth. Apply stain within 2 hours of application.

LIMITATIONS

Not intended for exterior use. Do not expose this product to excessive heat. Do not use over non-wood surfaces. Do not use over stained surfaces. Close container after each use. Not for use on floors. Do not thin.

ENVIRONMENTAL VARIABLES

Apply stain within 2 hours of application. Coverage of 400-500 Sq. FT / Gallon

SIZES

One Quart, Half Pint

CLEAN-UP

Wash tools with mineral spirits or paint thinner immediately after applying.

CAUTIONS

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Flashpoint	Greater than 108°F (42°C)
Dry Film Thickness	0.25 – 0.50 mils
Wet Film Thickness	2.5 to 5.0 mils
Viscosity Range	10 – 20 Seconds #4 Ford Cup
VOC	720 g/L

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.