

PRODUCT

**Aerosol Premium Spar
Polyurethane Varnishes**

RECOMMENDED USES

A clear protective finish for exterior wood surfaces. Can be used over stained or bare wood.

FINISHES

Clear Satin SV39
Clear Semi-Gloss SV23

APPLICATION

Before spraying, shake can for 2 minutes after ball within start to rattle and occasionally during the use. Hold can 10 to 18 inches (25 to 45 cm) from the surface. Apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke. Keep can in motion while spraying. DO NOT apply over Lacquer or Shellac.

LIMITATIONS

Do not expose this product to excessive heat and flames.

ENVIRONMENTAL VARIABLES

Dry times at 70-80F and 50% humidity are set to touch in 20-30 minutes and tack free in 1 hour. Recoat after 1 hour. Dries overnight under normal conditions. High humidity or low temperature may increase dry time.

SIZES

11.5 OZ

CLEAN-UP

Never stick sharp objects into the opening at the top of the can. Use Mineral Spirit for cleaning spray tip and wet film. For dry film use Acetone or Paint Stripper or Toluene.

CAUTIONS

Protect unused product from freezing.

Disposal - Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

PHYSICAL PROPERTIES

Dry Time at 60°	80-100
VOC	0.85 / 67%

Revised: 05/2023

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since GPM does not control the application of its products, or the condition of the surfaces to which they are applied, GPM's liability will under no circumstances exceed replacement of the product.