Safety Data Sheet

1. Identification

Product Information: FM-11

Product Name: Painter's Select Specialty Latex Field Marking (Green)

Recommended Use: Exterior Flat Latex Paint

Application Method: No Information

GPM Supplied by:

201 Jandus Road Cary, IL 60013

Telephone: (847) 639-5383

Emergency Telephone: (866)257-3981

2. Hazards Identification

EMERGENCY OVERVIEW: No Information

GHS Classification

Carc. 1B

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

1% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

H350 Carcinogenicity, category 1B Suspected of causing cancer.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P281 Use personal protective equipment as required. P308+P313 IF exposed or concerned: Get medical advice/attention.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. % GHS Symbols	GHS Statements
LIMESTONE	1317-65-3	2.5-10 No Information	No Information
TITANIUM DIOXIDE	13463-67-7	2.5-10 No Information	No Information
CELLULOSE	9004-34-6	1.0-2.5 No Information	No Information
DISTILLATES (PETROLEUM), HYDROTREATED	64742-54-7	0.1-1.0 GHS08	H350
HEAVY PARAFF			
HYDRATED ALUMINUM MAGNESIUM SILICATE	12174-11-7	0.1-1.0 No Information	No Information

HYDRATED ALUMINUM MAGNESIUM SILICATE 12174-11-7 0.1-1.0 No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

FIRST AID - EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

FIRST AID - INGESTION: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to 10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

SPECIAL FIREFIGHTING PROCEDURES: Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

6. Accidental Release Measures

ENVIRONMENTAL PRECAUTIONS: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

7. Handling and Storage





HANDLING: KEEP FROM FREEZING

STORAGE: Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
LIMESTONE	10 mg/m3 Total Dust	N.E.	15 mg/m3 Total Dust	N.E.
TITANIUM DIOXIDE	10 mg/m3	N.E.	15 mg/m3	N.E.
CELLULOSE	10 mg/m3 (Total Dust)	N.E.	5 mg/m3 (Respirable dust)	N.E.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFF	5 mg/m3	10 mg/m3	5 mg/m3	N.E.
HYDRATED ALUMINUM MAGNESIUM SILICATE	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



SKIN PROTECTION: Sensitive individuals should wear gloves to prevent repeated contact.



EYE PROTECTION: Safety glasses with side-shields



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: Wash hands before eating, drinking, or smoking.

9. Physical and Chemical Properties

Appearance: Thick Green Liquid Physical State: Liquid

Odor: **Odor Threshold:** No Information Slight Ammonia Density, g/cm3: 0.000 pH: No Information Freeze Point, °C: No Information Viscosity: No Information Solubility in Water: Partition Coefficient, n-octanol/ No Information No Information

Decomposition temperature, °C No Information water:

Boiling Range, °C: 98 - 104 Explosive Limits, %: N/A

Combustibility:Does not Support Combustion
Evaporation Rate:Flash Point, °C:Not Applicable
Auto-Ignition Temperature, °CNo InformationVapor Density:No InformationVapor Pressure, mmHg:No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND FREEZING.

INCOMPATIBILITY: No Information

HAZARDOUS DECOMPOSITION PRODUCTS: MAY GENERATE TOXIC OR IRRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

11. Toxicological Information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

EFFECT OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.

EFFECT OF OVEREXPOSURE - INGESTION: May be harmful if swallowed. May cause gastrointestinal disturbance.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Under normal use conditions, this product is not expected to cause adverse

health effects.

CARCINOGENICITY: IARC lists Titanium Dioxide as a possible human carcinogen (Group 2B)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> <u>Chemical Name</u> <u>Oral LD50</u> <u>Dermal LD50</u> <u>Vapor LC50</u>

(Rabbit)

1317-65-3 LIMESTONE 6450 mg/kg (Rat) > 2000 mg/kg N.I.

13463-67-7 TITANIUM DIOXIDE >24000 mg/kg >10000 mg/kg N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No Information

13. Disposal Information



Product

DISPOSAL METHOD: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: Not Regulated by DOT

DOT Proper Shipping Name:Not RegulatedPacking Group:Not RegulatedDOT Technical Name:Not RegulatedHazard SubClass:Not RegulatedDOT Hazard Class:Not RegulatedResp. Guide Page:No Information

DOT UN/NA Number: Not Regulated

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.AMMONIUM HYDROXIDE1336-21-6MAGNESIUM NITRATE10377-60-3

FORMALDEHYDE 50-00-0

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

 Chemical Name
 CAS-No.

 WATER
 7732-18-5

 NEPHELINE SYENITE
 37244-96-5

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

 Chemical Name
 CAS-No.

 WATER
 7732-18-5

 NEPHELINE SYENITE
 37244-96-5

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical NameCAS-No.TITANIUM DIOXIDE13463-67-7HYDRATED ALUMINUM MAGNESIUM SILICATE12174-11-7CRYSTALLINE SILICA14808-60-7FORMALDEHYDE50-00-0NAPHTHALENE91-20-3

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class No Information

16. Other Information

Revision Date: 7/22/2016 Supersedes Date: New MSDS

Reason for revision: No Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health: *1 Flammability: 0 Reactivity: 0 Personal Protection: N.I.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H350 Suspected of causing cancer.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.