



## Color Décor Spray Enamel

### DESCRIPTION

Economical interior/exterior decorative enamel spray at any angle, comfort spray tip.

### ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



### Color Décor Primer

**TYPE:** VT Alkyd

**VOC/MIR**

VOC & MIR COMPLIANT

Maximum 65% & 1.4 pw MIR for Gloss & Satin, 80% VOC & 1.9 pw MIR for metallic, 60% VOC & 1.2 pw MIR for Flat

**GLOSS AT 60°**

70-90 gloss, 15-25 Satin, 0-5 Flat

**PERCENT SOLIDS BY WEIGHT**

CDS-13 19.13%

### COLORS

CDS-1 Gloss White

CDS-2 Gloss Black

CDS-4 Blue

CDS-7 Brown

CDS-9 Silver

CDS-10 Wrought Iron Black

CDS-13 Satin White

CDS-19 Bright Red

CDS-20 Hunter Green

### Product Features

- Fast Drying
- Popular decorative colors
- Lasts Longer

### FLASH POINT

< 20° F.

### RECOMMENDED USE:

For wood, metal, furniture, handcrafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

**DRY TIME:** Set to touch in 5-10 minutes. Tack free in 10-20 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

**DISPOSAL:** Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

**CLEAN UP:** Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

**DISPOSAL:** To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to [www.Earth911.org](http://www.Earth911.org).

**STORAGE:** Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

### APPLICATION METHODS

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

### Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Color Décor or XOP Primer is recommended
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

### WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.