



GPM All Purpose Spray Enamel

DESCRIPTION

Very economical interior/exterior all purpose, fast drying enamel

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



All Purpose Flat

TYPE: VT Alkyd, very fast drying

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.4pw MIR for gloss enamels 60% VOC & 1.2 pw MIR for flat

GLOSS AT 60°

Flat Enamels: 0-5

Gloss Enamels 60-80

PERCENT SOLIDS BY WEIGHT 8.6%

COLOR

AGP-1 Gloss White

AGP-2 Gloss Black

AGP-3 Flat White

AGP-4 Flat Black

FLASH POINT

< 20° F.

Product Features

- Fast Drying

RECOMMENDED USE: Wood, metal, furniture, handcrafts and other paintable surfaces

DRY TIME: Set to touch in 0-5 minutes. Tack free in 5-15 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new clean surface no primer is necessary. For rusty metal surfaces prime with X-O Rust Primer.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.