

# EASYCARE<sup>®</sup>

## Premium Décor Decorative Finish Camouflage

### DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

### ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



### • PDS Premium Décor Flat

- TYPE: decorative, fast drying
- VOC & MIR COMPLIANT
- Maximum 60% VOC & 0.80 pw MIR for flat
- enamels.
- GLOSS AT 60° Flat Enamels: 0-5
- PERCENT SOLIDS BY WEIGHT 20.45% + - 2

### PRODUCT FEATURES

- Fast Drying
- Camouflage colors
- Lasts Longer

### COLORS & BASES

- PDS-180 Light Khaki
- PDS-181 Forest Green
- PDS-182 Military Green
- PDS-183 Dark Brown
- PDS-184 Black

### FLASH POINT

< 20° F.

### RECOMMENDED USE

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

**DRY TIME:** Dry to touch in 0-10 minutes. Tack free 20-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

**DISPOSAL:** Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

**CLEAN UP:** Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

**STORAGE:** Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

### APPLICATION METHOD

- Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use.
- Hold can 10" to 18" (25 to 45 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke.
- Keep can in motion while spraying.
- Recoat within one hour.

### SURFACE PREP

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

### WARNINGS

Contains propane, acetone and aromatic solvents. Extremely flammable.

Storage and handling: Level-3 Aerosols.