

EASYCARE[®]

Premium Décor High Heat

DESCRIPTION

Superior interior/exterior high heat enamel spray at any angle, comfort spray tip. Takes heat up to 1000°F.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



- **Premium Décor High Heat**
- VOC & MIR COMPLIANT
- Maximum 80% VOC & 1.85 pw MIR for aluminum for Flat White & Flat Black
- **GLOSS AT 60°** White & Flat Black: 0-10
- **PERCENT SOLIDS BY WEIGHT:** 22.40% + - 2
- PDS 1550

PRODUCT FEATURES

- Fast Drying
- Takes heat up to 1000° F
- Lasts Longer

COLORS & BASES

PDS-1550 Aluminum
PDS-1551 Flat White
PDS-1552 Flat Black

FLASH POINT

< 20° F.

RECOMMENDED USE

For interior or exterior surfaces such as barbecues, car engines, boilers, heaters, steam pipes and furnaces. Will not with-stand open flame. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Flat White & Black: Set to touch in 20-50 minutes. Tack free in 3-4 hours. Aluminum set to touch in 5-10 minutes. Tack free in 10-30 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHOD

- Before spraying, shake can for two minutes after ball within begins to rattle. Shake can occasionally during use
- Hold can 10" to 18" (25 to 45 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

SURFACE PREP

- Remove all grease, oil, dirt, wax and rust scale from surface.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.