

# EASYCARE

## Premium Décor Lacquer

### DESCRIPTION

Superior interior/external decorative lacquer enamel spray at any angle, comfort spray tip. Great for use on wood, metal and furniture. Easy to sand.

### ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



- **Premium Décor Lacquer**
- **TYPE:** Genuine lacquer
- **VOC/MIR**
- VOC & MIR COMPLIANT
- Maximum 65% VOC & 0.95 pw MIR for PD1353 & PD 1354 (Black & White
- Maximum 67% VOC & 0.85 pw MIR for PD1355 Clear
- **GLOSS AT 60°**Gloss Enamels: 80 MIN
- **PERCENT SOLIDS BY WEIGHT :** 15.45% + - 2
- PDS-1353

### PRODUCT FEATURES

- Fast Drying
- High Gloss
- Lasts Longer

### COLORS & BASES

- PDS-1353 Black
- PDS-1354 White
- PDS-1355 Clear

### FLASH POINT

< 20° F.

### RECOMMENDED USE

For wood, metal, furniture, tools, handcrafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

**DRY TIME:** Set to touch in 5-20 minutes. Tack free in 15-45 minutes. Recoat anytime. High humidity or low temperature may increase dry time.

**DISPOSAL:** Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**CLEAN UP:** Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

**STORAGE:** Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

### APPLICATION METHOD

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 18" (25 to 45 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

### SURFACE PREP

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

### WARNINGS

Contains propane, acetone and aromatic solvents & petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.