

EASYCARE

Premium Décor Metallic



DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer

- **Premium Décor Metallic**
- TYPE: Metallic spray finishes, fast drying resists rust
- VOC/MIR
- VOC & MIR COMPLIANT
- Maximum 80% VOC & 1.25 pw MIR
- GLOSS AT 60°
- Brilliant
- PERCENT SOLIDS BY WEIGHT :
- PDS-90 21.0% + - 2

PRODUCT FEATURES

- Fast Drying
- Popular metallic colors
- Spray at any angle comfort tip
- Lasts Longer

COLORS & BASES

- PDS-87 Rose Gold
- PDS-88 Brushed Nickel
- PDS-89 Oil Rubbed Bronze
- PDS-90 Silver
- PDS-92 Copper
- PDS-91 Gold
- PDS-94 Chrome

FLASH POINT

< 20° F.

RECOMMENDED USE

All types of metal, wood and ornamental pieces, picture frames, handcrafts and other art objects. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Dry to touch in 5-10 minutes. Tack free in 10-20 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHOD

- Before spraying, shake can for 2 minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 18" (25 to 45 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

SURFACE PREP

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.