

EASYCARE

Premium Décor Decorative Finish Satin Enamel



DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer

- **PDS Premium Décor Satin**
- **TYPE:** decorative, fast drying
- VOC & MIR COMPLIANT
- Maximum 65% VOC & 0.95 pw MIR for satin enamels.
- **GLOSS AT 60°**
- Satin Enamels: 15-40
- **PERCENT SOLIDS BY WEIGHT** 19.65% + - 2

PRODUCT FEATURES

- Fast Drying
- Popular decorative colors
- Lasts Longer

COLORS & BASES

PDS-3 Satin White	PDS-115 Wild Rapids	PDS-123 Pink Pale
PDS-4 Satin Black	PDS-116 Almond	PDS-125 Fossil
PDS-8 Clear Acrylic Satin	PDS-117 Cabin Fever	PDS-126 Currant
PDS-113 Goldfish	PDS-118 Marshmallow	PDS-127 Sour Apple
PDS-114 Sea Seeker	PDS-119 Gibraltar	PDS-128 Lady Bug
	PDS-120 Gale Winds	PDS-150 Hunter Green
		PDS-151 Resin Tan
		PDS-152 Burgundy
		PDS-153 Army Green
		PDS-154 Khaki

RECOMMENDED USE

For interior or exterior wood, metal, furniture, hand crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Set to touch in 0-10 minutes. Tack free 20-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHOD

- Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use.
- Hold can 10" to 18" (25 to 45 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke.
- Keep can in motion while spraying.
- Recoat within one hour.

SURFACE PREP

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: