



Floor Stripper

DESCRIPTION

Professional strength Floor Stripper dissolves old film. Removes old waxes, finishes and sealers.

TV-34 FORMULA

Percent solids by weight: 12 to 14.5%

Viscosity: Water thin

Weight per US gallon: 8.8 +/- 0.1 lb

- Ammonia-free, fresh scent
- Effective, fast acting formula

RECOMMENDED USE: Removes all acrylic and wax based floor finishes along with soil, grease and grime. Also works as a degreaser.

HELPFUL HINTS: DO NOT USE ON ALUMINUM, WOOD, GLASS OR MARBLE. Test in inconspicuous area to check for effectiveness and compatibility with surface.

DISPOSAL: Use up or give away excess product. Contains surfactants. Do not reuse container. Empty container may be recycled or placed in trash.

HANDLING & STORAGE: Avoid extreme temperatures. Store in a cool, dry area. Close container after each use. If frozen, thaw and mix before use. Do not mix with bleach or any other household chemicals.

APPLICATION METHODS: Add 16 oz. (473 ml) or less to one gallon (3.78L) of hot water depending on surface condition. Uniformly apply solution to floor, but do not flood. Soak for 15 minutes, avoiding walking on surface during that time. Scrub thoroughly with floor machine, mop or carefully selected pad (some pads may scratch pure vinyl or linoleum). Pick up stripper before it dries. Rinse with cold water. Second application or stronger solution may be necessary on difficult surfaces.

CAUTION

- Use rubber gloves and goggles to avoid irritation.
- Do not allow contact with eyes and skin.
- Keep children and pets away from working area