



Floor Finish

DESCRIPTION

High Solids Floor Finish is fast drying, durable and resistant to detergent and scratching. Recommended for high speed, dry buff.

M-33 FORMULA

Percent solids by weight: 25%

Viscosity: Water thin

Weight per US Gallon: 8.58 +/- 0.1lb

Product Features

- Recommended for high speed, dry buff or spray buff maintenance methods
- Fast drying, durable finish resistant to detergent and scratching
- Excellent slip resistance for use on resilient and non-resilient floors
- UL registered

RECOMMENDED USE: All types of resilient flooring including vinyl, vinyl composite, linoleum, asphalt or rubber tile, as well as sealed surfaces such as terrazzo, concrete, wood and cork.

HELPFUL HINTS: Avoid flooding against baseboards or under furniture. Test in inconspicuous area to check for appearance and compatibility with surface. If appearance of floor is good, wash with Neutral Cleaner or All Purpose Cleaner. Strip questionable finishes with Floor Stripper, following label directions, then rinse thoroughly. Apply on dry surface.

COVERAGE: One gallon (3.78L) covers 2,000 square feet (180 square meters). When dry, buff surface at high speed for best results

CLEAN UP: N/A

DISPOSAL: Use up or give away excess product . Contains surfactants. Do not reuse container. Empty container may be recycled or placed in trash.

HANDLING & STORAGE: Avoid extreme temperatures. Store in a cool, dry area. Close container after each use. If frozen, thaw and mix before use.

APPLICATION METHODS: Apply new finish with mop, sponge or lambs wool pad. When applying more than one coat surface must be completely dry (20 to 40 minutes).

-
- Avoid contact with eyes and skin.
 - Use of rubber gloves are recommended to avoid irritation