

EASYCARE.

Platinum Paint and Primer in One Exterior Satin Finish

DESCRIPTION

Best quality exterior 100% acrylic latex satin finish house & trim paint with low temp applications and a Lifetime warranty when applied according to all label directions on a properly prepared surface.

• WAES-P FORMULA ANALYSIS

- Resin Type-Acrylic
- Sheen/Type Finish:
- 10-20 @60° / Satin
- Weight per Gallon = 10.2 lbs. \pm .2
- Percent Solids by Weight = 46.7 % \pm .2%
- Percent Solids by volume = 36.6 % \pm .2%
- Viscosity Range = 95-105 KU
- V.O.C. = Less than 50 g/l 0.42 lbs./gal.
- MPI Certification - # 15

RECOMMENDED USE

Previously painted or primed exterior surfaces, including properly prepared wood, vinyl, aluminum and factory primed siding. This product is Master Painter Institute certified and approved for use by the United States Government. .

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries in 1-2 hours at 77°F and 50% humidity. Recoat if necessary after overnight dry. High humidity or low temperature may increase dry time. Darker colors may require additional dry time between coats. Dry paint film is mildew resistant

COVERAGE: 350-400 sq.. per gallon depending on the porosity of the surface to be painted.

CLEAN UP & DISPOSAL: Wash tools with warm water and soap immediately after applying. Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHOD

This paint can be used over latex or oil based paint. Intermix all containers for color uniformity. Stir thoroughly before and during use. Certain colors may require more than one coat. Do not apply over a surface that has not been properly prepared. Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 40°. Use product when surface and air temperature are between 35-90°. Do not apply in hot sun; follow shade around house. Do not over spread. Use a premium brush or pad applicator. If spray applied back brushing is recommended to assure adequate penetration into the substrate . For best performance; apply two coats on new surfaces after priming. Allow new masonry to cure at least 30 days before coating

SURFACE PREP

See "Surface Prep" section for recommendations



PRODUCT FEATURES

- Durable one-coat coverage with exceptional hide
- 100% Acrylic low temp application 35°
- Superior fade resistance
- Mildew resistant coating
- High Hiding formula for excellent coverage
- Easy soap & water clean-up
- Lifetime warranty

COLORS & TINTING

Colors Available:

- WAES-1 Jamestown Red
- WAES-2 Black
- WAES-6 Hunter Green
- WAES-9 White
- WAES-17 Tudor Brown

Bases Available:

- WAES-P Pastel Base
- WAES-T Tint Base
- WAES-D Deep Base
- WAES-N Neutral Base