

EASYCARE[®]

Paint & Primer In One Interior Semi-Gloss Finish

DESCRIPTION

A durable 100% acrylic latex satin paint with a 15 year warranty when applied according to all label directions on a properly prepared surface.

ECS FORMULA ANALYSIS

Resin Type- Acrylic

Sheen/Type Finish:

45-60 @60° / Semi-Gloss

Weight per Gallon = 10.3 lbs/gal

Percent Solids by Weight = 48.7 % ± .2

Percent Solids by volume = 37.7 % ± %2

Viscosity Range = 90-100

V.O.C. = Less than 5 g/L



PRODUCT FEATURES

- Fade resistant
- Washable
- Easy soap & water clean-up

BASES AVAILABLE

- ECS-P Patel Base
- ECS-T Tint Base
- ECS-D Deep Base
- ECS-N Neutral Base

RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces.

THINNING: Thin sparingly with water if necessary for spray application.

DRY TIME: Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant.

COVERAGE: 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHOD

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

SURFACE PREP

See "Surface Prep" section for recommendations