

EASYCARE

EasyCare Interior Ceiling Paint EZF-2

DESCRIPTION

A premium interior acrylic paint that is designed to meet the highest expectations of the most demanding consumer.

EZF-2 FORMULA ANALYSIS
Resin Type-Vinyl Acrylic /Acrylic
Sheen/Type Finish:
1-3 @60° / Flat
Weight per Gallon = 11.72 lbs/gal
Percent Solids by Weight = 52.0%
Percent Solids by volume = 34.0 %
Viscosity Range = 100-105 KU
V.O.C. = Less than 5 g/L
Coverage=350-400 sq. ft. per gallon.
MPI Certification - # 53



PRODUCT FEATURES

- Hides Ceiling Defects
- Ultra Flat Finish
- Spatter Resistant
- High Hiding Formula
- Low Odor, Low VOC
- Mildew Resistant Finish

RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces. This product is Master Painter Institute certified and is approved for use by the United States Government.

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries to the touch in 2-4 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry Paint film is mildew resistant.

COVERAGE: 350-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying. Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHOD

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

SURFACE PREP

See "Surface Prep" section for recommendations