

EASYCARE[™]

Paint & Primer Interior Satin Finish

DESCRIPTION

A durable 100% acrylic latex satin paint with a 15 year warranty when applied according to all label directions on a properly prepared surface.

ECSE FORMULA ANALYSIS

Resin Type-Acrylic Latex

Sheen/Type Finish: 25-35 @60° / Satin

Weight per Gallon = 13.0 lbs. \pm .2

Percent Solids by Weight = 46.4 % \pm 2%

Percent Solids by volume = 35.0 % \pm 2%

Viscosity Range = 90-100

V.O.C. = Less than 5 g/L



PRODUCT FEATURES

- Fade resistant
- Washable
- Easy soap & water clean-up

BASES AVAILABLE

- ECSE-P Pastel Base
- ECSE-T Tint Base
- ECSE-D Deep Base
- ECSE-N Neutral Base

RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces.

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries to the touch in 1-2 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

COVERAGE: 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP & DISPOSAL: Wash tools with warm water and soap immediately after applying. Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHOD

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

SURFACE PREP

See "Surface Prep" section for recommendations