

# EASYCARE<sup>®</sup>

## Interior Ceiling Paint

### DESCRIPTION

A water based acrylic ceiling paint with a 15 year warranty when applied according to all label directions on a properly prepared surface.

### CBW FORMULA ANALYSIS

Sheen/Type Finish: Acrylic

1-3 @60° / Flat

Weight per Gallon = 11.3 lbs/gal

Percent Solids by Weight = 48.0 ± .2

Percent Solids by volume = 28.5% ± 2%

Viscosity Range = 95-100

V.O.C. = Less than 5 g/L

PVC 72.5%



### PRODUCT FEATURES

- Non-Spatter Formula
- Ultra Flat Finish
- Hides Minor Imperfections
- Quick Dry

### COLOR AVAILABLE

CBW Bright White

### RECOMMENDED USE

Previously painted or properly prepared and primed interior ceilings. Hides Minor imperfections.

**THINNING:** Thin sparingly with water if necessary for spray application.

**DRY TIME:** Dries to the touch in 1-2 hours at 77° and 50% humidity. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Darker colors may require additional dry time between coats. Dry Paint film is mildew resistant.

**COVERAGE:** 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

**STORAGE:** Protect unused product from freezing.

### APPLICATION METHOD

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

### SURFACE PREP

Remove loose paint, wash off dirt and grease with proper cleaning solution.

Scuff sand and dull glossy surfaces.

Patch cracks and holes and spot primer

For heavily stained areas primer with a stain blocking primer (SRL-1).

### SURFACE PREP

See "Surface Prep" section for recommendations