

LEGENDARY PERFORMANCE

Mythic

PAINT

Classic



INTERIOR FLAT

- SUPERIOR ADHESION
- LOW ODOR
- EXCELLENT WEATHERABILITY
- FAST DRY TIME



INTERIOR EGGSHELL

- VARIETY OF INTERIOR SURFACES
- SUPERIOR ADHESION
- LOW ODOR
- MILDEW AND FADE RESISTANT



INTERIOR SEMI-GLOSS

- SUPERIOR ADHESION
- LOW ODOR
- MILDEW AND FADE RESISTANT
- EXCELLENT GLOSS RETENTION

Mythic Classic™ Interior paint provides durable, fade and mildew resistant protection for a variety of interior surfaces with low VOC's. Stronger, safer, smarter paint. Now that's a breath of fresh air.

Low VOC
Volatile Organic Compounds
Excluding addition of colorant (untinted)



Classic

INTERIOR PRODUCTS

EQUIPMENT/PERTRECHOS

Conv. Spray:	40 PSI TIP:704/FX	Pistola convencional:	40 PSI TIP:704/FX
Airless Spray:	1800 - 2400 PSI TIP: .015" - .021"	Pistola sin aire:	1800 - 2400 PSI TIP: .015" - .021"
Brush:	Polyester or Nylon	Pincel:	Poliéster or Nylon
Roller:	1/4" - 1/2" Nap Cover	Rodillo:	1/4" - 1/2" Nap Cubieta
Pad:	Standard	Pad::	Estándar

THINNER & CLEAN UP/DILUYENTE Y LIMPIEZA

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.
 No se recomienda diluir, pero si es necesario utilizar, limpiar el agua con moderación. El jabón y el agua de limpieza.

SURFACE PREP/PREPARACIÓN DE LA SUPERFICIE

Clean all surfaces to be painted and remove all dirt, grease, oil, fingerprints, mildew, waxes, etc. Rinse and allow the surface to dry. Fill in holes or cracks with appropriate patching material. Glossy surfaces should be dulled by sanding. Remove all dust and loose material before priming. Use MP730 Mythic All Purpose Primer to seal stains caused by water, smoke, ink, pencil, grease, etc. See Lead Paint Precautions for surfaces older than 1978. See product labels for additional information.

Raspe todas las superficies que va a pintar y elimine toda la suciedad, grasa, aceite, marcas de dedos, moho, ceras, etc. Enjuague y deje que se seque la superficie. Llene los agujeros o grietas con material adecuado para relleno. Las superficies brillantes deben deslustrarse con lija. Quite todo el polvo y material suelto antes de colocar la capa base. Utilice la Capa base para todo propósito MP730 Mythic para sellar manchas ocasionadas por agua, humo, tinta, lápiz, grasa, etc. Consulte las Precauciones de pintura de plomo para superficies anteriores a 1978.

LIMITATIONS/LIMITACIONES

- KEEP FROM FREEZING
- Low temperatures and high humidity may increase dry time.
- NO EXPONER A TEMERATURAS DE CONGALAMIENTO
- No exponer a temperaturas de congelamiento

PACKAGING/EMBALAJE

Quarts, Gallons, depending on product type.
 Cuartos de galón, galones, dependiendo del tipo de producto.

COLORS/COLORES

- 1288 palette colors
- Computer color matching available
- 1288 colores de la paleta
- Color Computer juego disponible

SPECIFICATION DATA/ESPECIFICACIONES TECNICAS*

Product	Interior Flat MP100	Interior Eggshell MP101	Interior Semi-Gloss M1202	Producto
Type	Acrylic Latex			Tipo
Finish	1-5 @85°	10-20 @60°	45-60 @60°	Acabado
Volume Solids	45 ±2%	36 ±2%	48.7 ±2%	Volumen Sólido
Wt./Gallon	11.7 lbs ±2	10.4 lbs ±2	10.25 lbs ±2	Peso/galón
VOC (max)	Less than 5 g/L			VOC (máximo)
Dry Time	Touch: 2 hours; Recoat: 4 hours @ 77°F, 50% RH			Tiempo de secado
Coverage	250-400 sq ft/gal sq. ft. per gallon			Cobertura