



# Painter's Select Everyday Interior Semi-Gloss Finish

## DESCRIPTION

A quality interior vinyl acrylic paint. This low odor, environmentally friendly product is stain resistant and scrubbable.

JS FORMULA ANALYSIS
Resin Type-Vinyl Acrylic
Sheen/Type Finish: 35-55 @60° / Semi-Gloss
Weight per Gallon = 10.30 lbs/gal
Percent Solids by Weight = 40.0 %
Percent Solids by volume = 24.0%
Viscosity Range = 95-100 KU
V.O.C. = Less than 50 g/L
Coverage= 250-400 sq. ft. per gallon

### Product Features

- Scrubbable
- Low Odor
- Low VOC
- Mildew Resistant Finish

### Colors/Bases

- Available:**
- JS-1 White
  - JS-P Pastel Base
  - JS-T Tint Base
  - JS-D Deep Base
  - JS-N Neutral Base

## RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces. Perfect for kitchens, bathrooms, and areas that need constant washings

**THINNING:** Thin sparingly with water if necessary for spraying.

**DRY TIME:** Dries to the touch in 2-4 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

**COVERAGE:** 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**STORAGE:** Protect unused product from freezing.

## APPLICATION METHODS

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

## SURFACE PREP

- Remove loose paint, wash off dirt and grease with detergent.
- Remove wallpaper
- Scuff sand and dull glossy surfaces.
- Patch cracks and holes and spot prime.
- For heavily stain areas prime with Start Right Stain Blocking Primer (SRL-1).
- For drastic color changes or deep, vivid colors prime with Start Right Dark Color Primer (BC-1) tinted to the recommended color.