

# EASYCARE.

## Interior Water-Based PVA Drywall Primer

### DESCRIPTION

PVA Latex Primer is an excellent choice for priming new or unsealed drywall, ceilings, non-staining wood, plaster, stone, brick and concrete

#### • PVA-1 FORMULA ANALYSIS

- Resin Type-Vinyl Acrylic Latex
- Sheen/Type Finish:
- 2-4 @60° / Primer
- Weight per Gallon = 11.0 lbs..± .2
- Percent Solids by Weight = 44.9% .± 2 %
- Percent Solids by Volume = 26.9 % .± 2 %
- Viscosity Range = 95-105 KU
- V.O.C. = Less than 100 g/L

### RECOMMENDED USE

New or unsealed interior drywall, non-staining wood, plaster, brick, stone and concrete surfaces.

**THINNING:** Use as is.

**DRY TIME:** Dries in 1/2 hour. Topcoat after 2 hours. Allow 24 hours before sanding. Low temperature or high humidity may increase dry time.

**COVERAGE:** Average coverage 350 sq. ft. per gallon.

**CLEAN UP & STORAGE:** Use warm water and soap. Protect unused product from freezing.

**DISPOSAL:** Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program.

### APPLICATION METHOD

- Stir thoroughly before and during use.
- Do not apply over a surface that has not been properly prepared.
- Use product when surface and air temperature are between 50F° – 90F°.
- Do not over spread.
- Use a high quality 3/8 inch nap roller cover or nylon/polyester brush.
- If applying by roller, roll from dry area into the wet using firm crisscrossing strokes. Finish with long ceiling to floor strokes in one direction.
- Paint the ceiling first, then the walls.
- Allow new masonry to cure at least 30 days before coating.

### SURFACE PREP

- Remove loose paint, wash off dirt and grease with detergent. Allow to thoroughly dry.
- Scuff-sand and dull glossy surfaces.
- For best results on heavily stained areas, use a coat of Stain Blocking Primer (SRL-1).
- Do not use under semi-gloss or gloss paint.



### PRODUCT FEATURES

- Seals new drywall
- Soap & water clean-up
- Quick dry time

### COLORS

PVA-1 White