



Painter's Select Specialty Interior/Exterior Latex Block Filler

DESCRIPTION

A durable latex interior/exterior block filler for use on brick, concrete block and concrete. Fills holes and small cracks.

ABF-1 FORMULA ANALYSIS

Resin Type- Vinyl Acrylic

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 13.91 lbs.

Percent Solids by Weight = 69.0 %

Percent Solids by volume = 49.0 %

Viscosity Range = 120-130 KU

V.O.C. = Less than 50 g/L

Coverage=100 sq. ft. per gallon

Product Features

- Soap and water clean-up
- Quick Dry

Colors Available:

ABF-1 White

RECOMMENDED USE

To fill in cracks and small holes in concrete or similar surfaces resulting in a smooth, uniform finish.

THINNING: Do NOT Thin.

DRY TIME: Dries in 3 to 4 hours. High humidity may increase dry time.

COVERAGE: 100 sq. ft. per gallon.

CLEAN UP: Clean immediately with soap and water.

DISPOSAL: Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

APPLICATION METHODS

- Stir or mix block filler before using.
- Apply as is with brush, roller or paint pad.
- Do not overspread.
- Apply 1 to 2 coats allowing 3 to 4 hours between coats.
- Avoid painting if air or surface temperature could drop below 50° F (10°C) within 12 hours or if rain is expected.

SURFACE PREP

- Remove dirt, grease, mildew, loose or peeling paint, wax and soap residue.
- Dull glossy areas with sandpaper. Use an appropriate concrete or stucco patch for large cracks or holes.