



Painter's Select Specialty Exterior Oil Base Flat Barn & Fence

DESCRIPTION

Durable oil base barn & fence paint is harmless to livestock.

860 FORMULA ANALYSIS

Resin Type- Alkyd

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 10.77 lbs.

Percent Solids by Weight = 58.0%

Percent Solids by volume = 41.0%

Viscosity Range = 90-100

V.O.C. = Less than 250 g/L

Coverage=350-400 sq. ft. per gallon

Product Features

- Penetrates wood surfaces
- Durable

Colors Available:

860 Ranch Red

RECOMMENDED USE

All barns, fences, sheds and other exterior ranch and industrial buildings.

THINNING: Do NOT Thin.

DRY TIME: Dries thoroughly usually within 24 hours. High humidity or low temperatures may increase dry time. Recoat after 24 hours.

COVERAGE: 350-400 sq. ft. per gallon depending on surface porosity.

CLEAN UP: Clean-up with mineral spirits (paint thinner). Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- Stir or mix before and during use. Intermix all containers for color uniformity.
- On unpainted or bare surfaces use an exterior oil based primer.
- Apply paint liberally using a brush, pad or spray. For spraying information contact your paint specialist.
- Avoid painting if outside or surface temperature could drop below 50°F (10°C) within 12 hours or if rain is expected.

SURFACE PREP

- Remove dirt, mildew, grease, wax, soap residue and loose and peeling paint.
- Glossy areas must be dulled by sanding.
- Correct all areas in need of repair, such as loose or broken siding, brittle caulk, clogged or leaking gutters.
- Putty all nail heads.
- Caulk all seams with a siliconized acrylic caulk.