



## Painter's Select Specialty Exterior Oil Base Gloss Barn & Fence

### DESCRIPTION

Durable oil base barn & fence paint harmless to livestock. Penetrates deep into wood.

#### 800 FORMULA ANALYSIS

Resin Type- Alkyd

Sheen/Type Finish:

60 + @60° High Gloss

Weight per Gallon = 9.85 lbs.

Percent Solids by Weight = 53.0%

Percent Solids by volume = 38.0%

Viscosity Range = 70-75

V.O.C. = Less than 250 g/L

Coverage=350-400 sq. ft. per gallon

#### Product Features

- Fade resistant Coating,
- Harmless to Livestock
- Soap and water clean-up

#### Colors Available:

800 White

820 Barn Red

850 Ranch Red

#### RECOMMENDED USE

Barns, fences, sheds and other exterior ranch and industrial buildings.

**THINNING:** Do NOT thin

**DRY TIME:** Dries thoroughly usually overnight. May recoat after 24 hours. High humidity or low temperature may increase dry time.

**COVERAGE:** 350 - 400 sq. ft. per gallon depending on surface porosity.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**STORAGE:** Protect unused product from freezing.

#### APPLICATION METHODS

- Stir or mix before and during use. Intermix all containers for color uniformity.
- On unpainted or bare surfaces use an exterior oil based primer.
- On concrete, brick and stucco, use two 2 coats of this product.
- Use a proper metal primer when painting bare metal. Apply paint liberally using a brush, pad or spray. For spraying information contact your paint specialist.
- Avoid painting if outside or surface temperature could drop below 50°F (10°C) within 12 hours or if rain is expected.

#### SURFACE PREP

- Remove dirt, mildew, grease, wax, soap residue and loose and peeling paint.
- Glossy areas must be dulled by sanding.
- Correct all areas in need of repair, such as loose or broken siding, brittle caulk, clogged or leaking gutters.
- Putty all nail heads. Caulk all seams with a siliconized acrylic caulk.